

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.

THIS PAGE BLANK (USPTO)



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :

A01G 7/06, 9/10

A1

(11) International Publication Number:

WO 00/42835

(43) International Publication Date:

27 July 2000 (27.07.00)

(21) International Application Number: PCT/IL00/00039

(22) International Filing Date: 20 January 2000 (20.01.00)

(30) Priority Data:

128207

24 January 1999 (24.01.99)

IL

(71) Applicant (for all designated States except US): BIO-OZ ADVANCED BIOTECHNOLOGICAL AGRICULTURE LTD. [IL/IL]; Kibbutz Nahal Oz, 85145 M.P. Hanegev (IL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CHEMO, Ronen [IL/IL]; Nahal Oz, 85145 M.P. Hanegev (IL). MAOZ, Itai [IL/IL]; Nahal Oz, 85145 M.P. Hanegev (IL). YARDEN, Gal [IL/IL]; Nahal Oz, 85145 M.P. Hanegev (IL).

(74) Agent: NOAM, Meir; P.O. Box 34335, 91342 Jerusalem (IL).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published

With international search report.

(54) Title: A MULTI-BARREL PLANT INOCULATION GUN

(57) Abstract

The present invention relates to multi-barrel plant inoculation gun for a rapid large-scale plant anti virus inoculation comprising: (a) liquid container for inoculum solution (27); (b) compressed-gas source; (c) at least one compressed-gas fast-discharge-container (28) having a gas inlet (34) connected to the compressed-gas source, and a gas outlet connected to a gas fast-discharge-valve (29); (d) plurality of jet-injection units (35) each comprised of a body (20) having a liquid inlet (24) connected to the liquid container (27), a gas inlet (23) connected to the gas fast-discharge-valve (29) and a jet-outlet (21) internally connected to the liquid and gas inlets; (e) control unit for triggering-on the fast-discharge-valve; (f) chassis for positioning and supporting said elements. Upon triggering-on, the fast-discharge-container discharges a powerful pulse of gas distributed simultaneously to the plurality of jet-injection units and brought to contact with the inoculum solution for accelerating and shooting inoculum solution by jets of gas from the jet-outlets into the inner tissues of the plants.



AM

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

A Multi-Barrel Plant Inoculation Gun

Field of the invention

The present invention relates to a multi-barrel plant inoculation gun (hereinafter called also: MBG) for a rapid large-scale plant anti virus inoculation. The MBG performs the plant anti virus inoculation by simultaneously shooting a plurality of compressed gas jets carrying inoculum solution particles into the inner tissues of plants within the gun's coverage area. The present invention further relates to a combination of the MBG and a conveying mechanism, wherein the conveying mechanism is either for conveying green-house plant trays to the shooting coverage area of the MBG, or for conveying the MBG along rows of plants in a green-house or any other treatment area.

Background of the invention

A well known method in the field of plant anti virus inoculation is the Cross Protection method. According to this method, the inoculation of a crop against a virulent strain of virus is achieved by infecting the crop with a mild strain of the same virus.

The mechanism by which cross protection operates is not yet fully understood, and there are different proposed hypotheses trying to explain it. Whatever the mechanism is, the present invention deals only with its practical implementation.

The aim of the MBG according to the present invention is to effectively inoculate large-scale crops (usually in a greenhouse) by the mild strain of virus, thus saving time and money, and improving the inoculation reliability.

Summary of the invention

The present invention relates to multi-barrel plant inoculation gun (MBG) for a rapid large-scale plant anti virus inoculation comprising;

- (a) liquid container for inoculum solution;
- (b) compressed-gas source;
- (c) at least one compressed-gas fast-discharge-container having a gas inlet connected to the said compressed-gas source, and a gas outlet connected to a gas fast-discharge-valve;
- (d) plurality of jet-injection units each comprised of a body having; a liquid inlet connected to the said liquid container; a gas inlet connected to the said gas fast-discharge-valve; and a jet-outlet (in the context of the present invention called also "barrel") internally connected to the said liquid and gas inlets;
- (e) control unit for triggering-on the fast-discharge valve;
- (f) chassis for positioning and supporting said elements and their inter-connections;

wherein triggering-on the fast-discharge valve, discharges from the fast-discharge-container a powerful pulse of gas distributed simultaneously to the plurality of jet-injection units through the respective pipes and brought to contact the inoculum solution received from the liquid-container through the respective pipes, for accelerating particles of inoculum-solution and shooting inoculum solution by jets of gas from the jet-outlets into the inner tissues of plants.

According to the preferred embodiment, the MBG is further comprising a conveyor for conveying green-house plant trays under its shooting coverage area.

According to the preferred embodiment the MBG has a computer means and a user-panel for controlling its operation according to operation modes predetermined by its manufacturer or by its user through the user-panel.

Preferably, the conveyor include sensor means supplying to the computer-means data concerning the presence or location of plant trays, and the computer means correlates the shooting of inoculum-carrying jets with the convey of plant trays.

Preferably, the liquid container is a pressure-container connected to the compressed-gas source and having a pressure regulator valve obtaining a constant predetermined pressure adapted to drive out the inoculum-solution from the container in the accurate essential flow useful for the current inoculation job. According to another embodiment, the liquid container works without pressure and supplies the inoculum-solution by means of gravity force or by means of a pump. Preferably, according to both said liquid-container arrangements, an electrical faucet buffers between the container and the jet-injection-units for an improved control on the inoculum-solution consumption.

Preferably, the liquid container include means for whirling the inoculum solution, such as a motored propeller, a gas pipe bubbling within the liquid, a vibration motor vibrating the container or other known whirling means.

Preferably, the pipe connection between the liquid container and the jet-injection units is equipped with a unidirectional valve preventing a reverse flow of liquid or gas which may result during the fast-discharge of a gas pulse.

Preferably, the jet-injection-units are positioned on a flat matrix plate having crosswise orifices arranged in lines and rows, such that each jet-outlet (barrel) of the jet-injection-units is fixed vertically within one orifice (preferably by using integral threading made in the plate material).

Preferably, the connection between the matrix plate and the chassis is through an adjustable telescopic mechanism (or other adjustable acceptable mechanism) allowing to change the height (and/or orientation) of the plate for an optimal adaptation to the type and arrangement of the inoculated plants.

According to another embodiment, the MBG is further comprising conveying means for being propelled along green-house plant rows.

In the context of the present invention the term "gas source" refers to any type of gas supplier known in the art, either if it is carried by the MBG chassis or it is an external unit connected to the MBG by means of a gas hose. It may be an air compressor, a gas reservoir, a gas cylinder. Preferably the gas is air, however other gas types may be used as well.

The MBG may comprise mechanical or electromechanical means for changing or adjusting the orientation, height or lateral position of the matrix-plate relatively to the chassis. Thus, the MBG can be adapted for use with various types of plants, (or plant trays) having different dimensions, shapes, planting arrangements, or inoculation requirements.

According to another variation, the MBG is further comprises sensor means adapted to recognize the presence of plants below the matrix-plate and transmitting this data to the controlling unit, for automatically activating the MBG shooting, or for halting the convey mechanism of the machine at the end of a plant row.

Preferably, the inoculum solution is a hetrogenic solution containing particles (such as carborundum particles) useful for insertion into the inner tissues of plants when accelerated by the compressed gas. Thus, preferably the MBG, further comprises means for whirling the inoculum solution (within the liquid container) for providing a homogenize dispersion of the particles within the solution. Such means are an electrical mixer, or a gas pipe ended near the bottom of the liquid container for mixing the liquid by means of gas flow.

Detailed description of the invention

The present invention will be further described in detail by Figures 1-3. These figures are solely intend to describe one preferred embodiment of the MBG according to the present invention, and in no manner intend to limit the scope of the invention.

Brief description of the figures:

Figure 1 illustrates an isometric view of a chassis and a plant-tray conveyor of an MBG according to the present invention.

Figure 2 illustrates a schematic diagram of three jet-injection unit of the MBG, and their associate connections as a part of a plurality of similar jet-injection units.

Figure 3 illustrates in detail a schematic diagram of the liquid-container of Figure 1.

Detailed description of the invention:

Figure 1 illustrates an isometric view of a chassis and a plant-tray conveyor of an MBG according to the present invention. In this embodiment the chassis is a wheeled table (1) comprised of a supporting frame (2) having wheels (3) allowing moving from place to place comfortably, and a plant conveyor having a conveying-belt (4), moving endlessly around a drive-cylinder (5) and a tense-cylinder (6). The drive-cylinder (5) is driven by an electrical-motor (7) and a transmission belt (8). The conveying belt (4) is tensed by the drive-cylinder (6), and its associate tense-mechanism (12). The frame height can be made changeable by including a telescopic mechanism (or other acceptable height-adjusting mechanism) to the upright supports of the frame. The MBG user may control the conveyor speed through a user-panel (9) which controls the speed of the motor (7). Plant trays placed on the conveying belt (4) right side, are conveyed to a coverage area of the MBG below the matrix-plate support (10). The relative height of the matrix-plate (not shown in this figure) is adjustable by a telescopic vertical support (11). The plant tray within the MBG coverage area is bombarded by the MBG and then conveyed to the left of the conveyor.

Mechanical sensor (13) (may be any other known sensor such as Photo-electric sensor) recognizes the presence of a treated (inoculated) plant tray and stops the conveyor until being removed. The inoculation can be made either during a successive convey, or during stops in the convey, as selected by the user through the user-panel (9).

Figure 2 illustrates a schematic diagram of three jet-injection units of the MBG, and their associate connections as a part of a plurality of similar jet-injection units. Each jet-injection unit (35) (illustrated in a vertical cross-section view) is comprised of a body (20) (20A)(20B) having; a liquid inlet (24), a gas inlet (23), and a jet-outlet (21) internally connected to the said liquid and gas inlets. The liquid inlet (24) is connected to the liquid container (27) through a pipe (24A), a unidirectional valve (25) and an electrical faucet (26). The electrical faucet controls the flow of inoculum solution to the illustrated jet injection units (35) and to a plurality of similar jet-injection units (not seen in this figure), through the main pipe (26A) and the pipe-junction (33) to which the plurality of said units are connected. The gas inlet (23) is connected to a gas fast-discharge-valve (29) together with the gas inlets of a plurality of similar units which all are connected through the same gas-pipe junction (32). The fast-discharge valve (29) is connected to a fast-discharge-container (28), supplying a pulse of compressed-air to all the injection-units connected to the junction (32), always when the fast discharge valve (29) is triggered-on. The fast-discharge-container (28) is fed with a gas from a gas source (not seen in this figure) through the gas inlet (34). The fast discharge valve (29) is a pneumatic valve controlled pneumatically by a pneumatic-control valve (30). The

pneumatic control valve (30) is triggered-on by an electric signal received from a computer means of the MBG. A plurality of fast discharge valves (29) are connected to the pneumatic control valve (30) through a pneumatic control junction (31), wherein the gas inlet of each fast-discharge valve (29) is connected to a particular fast-discharge-container, and the gas outlet of the same valve (29) is connected to a plurality of jet-injection units. Thus, the total number of jet-outlets (barrels) of the MBG is a multiplication of the number of jet-injection units connected to each single fast discharge valve (29) with the total number of the fast discharge valves. The exact number of jet-injection units connected commonly to a single fast discharge container (28) and associate valve (29) may be calculated by a designer as a function of the length and width of the gas pipes, the gas capacity of the containers (28), the characteristics of the valve (29) and the jet-injection units (20), and the required jet pressure at the jet-outlets.

The characteristics of the jet-injection unit are mainly resulting from the dimensions (aperture diameter and width) of the jet-outlet (21), through which pass the inoculation outlet jet. The aperture diameter is designed small enough such that inoculum solution cannot pass it without the push of a gas pulse received from the fast-discharge-container through the fast discharge valve. The electrical faucet (26) is opened periodically in the intervals between gas pulses, for supplying to all the injection-units a restricted dose of inoculum solution which is then delayed adjacent to the jet outlet aperture, waiting for the next pulse of gas.

Each jet injection unit is fixed in one from a plurality of transverse holes made in a matrix-plate (22) which a small part of it is seen in this figure

in a cross sectional view. The complete matrix-plate is to be positioned within the matrix-plate support (10) seen in Figure 1 with the jet outlets oriented downwardly. Preferably each jet injection unit is comprised of an upper part having the gas and the liquid inlets and a lower part having the jet outlet, both parts are screwed into the matrix plate transverse holes by means of matching screw-threads.

Figure 3 illustrates in detail a schematic diagram of the liquid-container (27) of Figure 1. This container is a pressure container comprised of a container body (41), a container cover (44), a mixer (40) driven by a piston motor (48) through the mixer shaft (49), a gas pressure inlet (47) having a pressure regulator valve (46), a security valve (45), and a liquid outlet (50) for supplying inoculum solution to the electrical faucet (26) of Figure 1. The heterogenic inoculum solution is whirled by the mixer for insuring its unity, and driven out through the outlet pipe (42) by means of the gas (43) pressuring the liquid in a constant pressure regulated by the regulator valve (46) and protected by the security valve (45). Thus, a controlled flow of inoculum solution is always provided to the jet-injection unit, without the influence of the remaining amount of liquid within the container.

Claims:

1. A multi-barrel plant inoculation gun for a rapid large-scale plant anti virus inoculation comprising;

- (a) liquid container for inoculum solution (27);
- (b) compressed-gas source;
- (c) at least one compressed-gas fast-discharge-container (28) having a gas inlet connected to the said compressed-gas source, and a gas outlet connected to a gas fast-discharge-valve (29);
- (d) plurality of jet-injection units (35) each comprised of a body (20) having; a liquid inlet (24) connected to the said liquid container; a gas inlet (23) connected to the said gas fast-discharge-valve (29); and a jet-outlet (21) internally connected to the said liquid and gas inlets;
- (e) control unit for triggering-on the fast-discharge valve;
- (f) chassis for positioning and supporting said elements and their inter-connections;

wherein triggering-on the fast-discharge valve (29), discharges from the fast-discharge-container (28) a powerful pulse of gas distributed simultaneously to the plurality of jet-injection units (35) through the respective pipes and brought to contact the inoculum solution received from the liquid-container (27) through the respective pipes, for accelerating particles of inoculum-solution and shooting inoculum solution carried by jets of gas from the jet-outlets (21) into the inner tissues of plants.

2. A multi-barrel plant inoculation gun according to claim 1, further comprising a conveyor for conveying green-house plant trays under its shooting coverage area.
3. A multi-barrel plant inoculation gun according to any of the previous claims, having a computer means and a user-panel for controlling its operation.
4. A multi-barrel plant inoculation gun according to any of the previous claims, further comprising sensor means supplying to the computer-means data concerning the presence or location of plant trays, and the computer means correlates the shooting of inoculum-carrying jets with the convey of plant trays.
5. A multi-barrel plant inoculation gun according to any of the previous claims, wherein the liquid container is a pressure-container connected to the compressed-gas source and having a pressure regulator valve obtaining a constant predetermined pressure adapted to drive out the inoculum-solution from the container in the accurate essential flow useful for the current inoculation job.
6. A multi-barrel plant inoculation gun according to any of the previous claims, having an electrical faucet buffers between the container and the jet-injection-units for controlling the consumption of inoculum-solution.
7. A multi-barrel plant inoculation gun according to any of the previous claims, wherein the liquid container include whirling means for whirling the inoculum solution.

8. A multi-barrel plant inoculation gun according to any of the previous claims, wherein the pipe connection between the liquid container and the jet-injection units is equipped with a unidirectional valve preventing a reverse flow of liquid or gas which may result during the fast-discharge of a gas pulse.
9. A multi-barrel plant inoculation gun according to any of the previous claims, wherein the jet-injection-units are positioned on a flat matrix plate having crosswise orifices arranged in lines and rows, such that each jet-outlet of the jet-injection-units is fixed vertically within one orifice.
10. A multi-barrel plant inoculation gun according to any of the previous claims, wherein the connection between the matrix plate and the chassis is through an adjustable mechanism allowing to change the height of the plate for an optimal adaptation to the type and arrangement of the inoculated plants.
11. A multi-barrel plant inoculation gun according to any of the previous claims, further comprising conveying means for being propelled along green-house plant rows.
12. A multi-barrel plant inoculation gun according to any of the previous claims, further comprising sensor means adapted to recognize the presence of plants below the matrix-plate and transmitting this data to the computer means.
13. A multi-barrel plant inoculation gun as herein before described and illustrated.




FIGURE 1




Figure 2




Figure 3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IL 00/00039

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A01G7/06 A01G9/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A01C A01G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>DATABASE WPI Section Ch, Week 197718 Derwent Publications Ltd., London, GB; Class C03, AN 1977-32073Y XP002134966 & JP 52 012795 B (INST PHYSICAL & CHEM RES), 9 April 1977 (1977-04-09) abstract</p>	1,2,13
A	<p>WO 96 05721 A (MONSANTO CO) 29 February 1996 (1996-02-29) page 11, line 15 -page 12, line 26 -/-</p>	1,13

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

6 April 2000

Date of mailing of the international search report

18/04/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Merckx, A

INTERNATIONAL SEARCH REPORT

International Application No

PCT/IL 00/00039

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>PATENT ABSTRACTS OF JAPAN vol. 1995, no. 11, 26 December 1995 (1995-12-26) & JP 07 203989 A (HAMAMATSU PHOTONICS KK), 8 August 1995 (1995-08-08) abstract</p> <p>-----</p>	2,3

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IL 00/00039

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 52012795 B	13-11-1974	JP 1129704 C JP 49118883 A	24-12-1982 13-11-1974
WO 9605721 A	29-02-1996	AT 189356 T AU 683771 B AU 3405895 A BR 9508620 A DE 69514924 D EP 0776155 A JP 10506269 T NZ 292319 A	15-02-2000 20-11-1997 14-03-1996 25-11-1997 09-03-2000 04-06-1997 23-06-1998 29-06-1999
JP 07203989 A	08-08-1995	NONE	

THIS PAGE BLANK (USPTO)